



HUDSON OIL CORPORATION

Bridging Businesses together

Ruchliwa 15, 02-182 Warszawa, Polska
KRS:0000407082
Nurkent microdistrict, house 5/15, Alatau
district, Almaty city postal code 050038
Kazakhstan
BIN: 180140025638

+48 7320 70488
+7775 265 16 29
www.hudsonoil.eu
info@hudsonoil.eu

STANDARD SPECIFICATION OF VIRGIN FUEL OIL D6

METHOD UNITS	TEST	RESULT	UNIT
ASTM D5002	Density and relative Density of Crude Oils Average API Gravity	29.7 (29.7) (Min)	API
ASTM D1298–99	Density @ 15 °C	0.87 (0.8775) (Max)	Kg/t
ASTM D97	Pour Point of Petroleum Products Pour Point Pour Point	< –33 (–36) (Below Zero) < –27.4 (–32.8) (Below Zero)	°C °F
ASTM D93–IP34	Pensky–Martens Closed Cup Flash Point Corrected Flash Point	117(137) (Min)	°F
ASTM D4294	Sulfur Content in Petroleum Products by EDXRF Sulfur Content	0.38 (0.358) (Max)	Wt%
ASTM D445	Kinematic/Dynamic Viscosity Kinematic Viscosity @ 122 °F/50 °C	17.83 (18.12) (Max)	Mm2/s
ASTM D6304	Water Content by Coulometric Karl Fisher Titration Water Content	0.20 (0.7) (Max)	Wt%
ASTM D482	Ash From Petroleum Products Average Ash	0.279 (1.007) (Max)	Wt%
ASTM D2161	Conversion of Kinematic Viscosity To SUS/SFS 1 Saybolt Furoi Viscosity 122 °F	10.9 SFS	(Max)
ASTM D5184	Aluminum and Silicon in Fuel Oils by ICP–AES or AAS Aluminum Content Silicone Content	102 (Max) 93 (Max)	Mg/Kg Mg/Kg
ASTM D95	Water by Distillation, Vol%	0.70 (Max)	Vol%
ASTM D4503.06	Carbon Residue	1.11 (Max)	Wt%
METHOD TEST RESULT UNITS			
IP 143 Asphlteness Heptane Insolubles			
	Asphlteness Content	0.08	Wt%
IP 501 Determination of AL, Si, V, Ni, Fe, Na, Ca, Zn, P in Fuel Oil–ICPES			
	Aluminum	372	mg/kg
	Silicon	187	mg/kg
	Sodium	117	mg/kg
	Vanadium	1	mg/kg
	Calcium	779	mg/kg
	Zinc	298	mg/kg
	Phosphorous	4176	mg/kg
	Iron	545	mg/kg