

HUDSON OIL CORPORATION


Bridging Businesses together

Ruchliwa 15, 02-182 Warszawa, Polska
KRS:0000407082
Nurkent microdistrict, house 5/15, Alatau
district, Almaty city postal code 050038
Kazakhstan
BIN: 180140025638

+48 7320 70488
+7775 265 16 29
www.hudsonoil.eu
info@hudsonoil.eu

STANDARD SPECIFICATION OF JET FUEL 54

COMPONENT	UNIT	MIN	MAX	METHOD
A: ADDITIVES:				
Antioxidant in hydro processed fuel	Mg/l	17	24	
Antioxidant non hydro processed fuel	Mg/l		24	
Static dissipater first doping ASA–3	Mg/l	24	1	
Stadis 450	Mg/l		3	
COMBUSTION PROPERTIES:				
Specific Energy, Net	Mj/kg	18.4		D4808
Smoke Point	mm	19		D1322
Luminomitter Number		45		D1740
Naphthalenes	% volume		3	D1840
Properties Unit		Result Test IP		ASTM
B: COMPOSITION:				
Appearance	Clear Bright			Visual
Total Acidity	mg KOH/g		0.01	D974/3242
Aromatics	% vol		22	D1318/1319
Sulphur, Total	% mass		0.30	D1266/2622
Sulphur, mercaptan	% mass		0.003	D3227
Colour, Saybolt				D156
Doctor, Test	Negative			D4952
C: VOLATILY				
Initial Boiling Point	Centigrade		Report	D86/96
10% vol at °C			240	
20% vol at °C			Report	
50% vol at °C			Report	
80% vol at °C			Report	
End Point	Centigrade		300	
Recovered Residuals	% vol		1.5	
Loss	% vol		1.5	



HUDSON OIL CORPORATION

Bridging Businesses together

Ruchliwa 15, 02-182 Warszawa, Polska
KRS:0000407082
Nurkent microdistrict, house 5/15, Alatau
district, Almaty city postal code 050038
Kazakhstan
BIN: 180140025638

+48 7320 70488
+7775 265 16 29
www.hudsonoil.eu
info@hudsonoil.eu

Flash Point	Centigrade		42	D56/3828
Density at 15 °C	Kg/m2	776/840	180/385	D1298
LOW TEMPERATURE PROPERTIES:				
Freezing Point	Centigrade		– 40	D2256
Viscosity @ –20 °C	°C	8.0		D455
D: CORROSION				
Corrosion, Copper (2 hrs at 100 °C)			1	D130
Corrosion, Silver (4hrs at 50 °C)			1	D150
E: STABILITY				
Thermal Stability Control, Temp. 280 °C			323	
Filter Pressure, Differential mm. Hg			25	
Tube Deposit Rating (Visual)			< 3	
F: CONTAMINATIONS				
Existent Gum	mg/100ml		7	D361
Water Reaction, Interface Rating			16	D1084
Fuel with Static dissipater additives	75			D3684
Fuel without Static dissipater additives	85			
G: CONDUCTIVITY				
Electrical Conductivity	P ³ /3		Report	

- * Summer from March to October (PP – 5.0 °C)
- * Summer from March to October (CP – 0.0 °C)
- * Winter from November to February (PP – 10.0 °C)
- * Winter from November to February (CP – 5.0 °C)